



VERSID, Inc.

WHERE TEMPERATURE ACQUISITION BEGINS



Featuring **Disney SyncLink™** Technology

TEMPERATURE ACQUISITION MODEL (TAM) VT-55

Featuring Disney SyncLink™ Technology

VT-55 SPECIFICATIONS

TEMPERATURE CALIBRATION

- Instantaneous reads with variation of less than 0.25 degrees from 0°F to 212°F (-18°C to 100°C)
- Provides full temperature range for type K thermocouple
- Accredited 17025 – Traceable to NIST, NPL, PTB

VERSID ASSURANCE

- Versid Auto-Calibration System™
- Versid Battery Control System™
- Versid Warranty (12 months)

COMPATIBILITY

- Windows // XP, Vista, 7, 8, Pocket PC, CE, Mobile
- Android // Version 2.6 and above
- Backward compatible with all existing BT-10 R/T software applications

ENCLOSURE

- Sealed to IP 54 rating
- Flame retardant ABS with UL 94 HB rating
- Dimensions: 5.74 x 1.82 x 1.31in. (145.80 x 46.23 x 33.27mm)
- RoHS/95/EC - WEEE/96/EC - Antimicrobial coated

TECHNICAL SPECIFICATIONS

Bluetooth // Secure communications, 128 bit encryption
Error correction for guaranteed packet delivery
Fully qualified Class 2 Bluetooth 2.1 + EDR module
Bluetooth SIG qualified / Output power + 4dBm

Range // Up to 300 ft (30m)

Charger // VC-55 Industrial 110v Mini USB
Options: US, UK, Australia, China

Approvals // **FC** **UL** **CE**

Electronics Operating Temperature // -40°F to 185°F
(-40°C to 85°C)

Call // 800.543.8532
Email // info@versid.com
Visit // www.versid.com

Versid, Inc.
PO Box 1236
Fruitland Park, FL 34731